

ISO9000/TS16949
DOT



MODEL	offset	center hole	bolt hole	pitch circle	gross weight	valve	Tyre Type
22.5x8.25	169	Ø281	10-Ø26	Ø335	46,2	V3-20-12	11R22.5
22.5x8.25	168	Ø222	10-Ø32	Ø285.75	47,2	V3-20-12	11R22.5
22.5x8.25	165	Ø221	8-Ø32	Ø285.75	46,8	V3-20-12	11R22.5
22.5x8.25	165	Ø222	10-Ø32	Ø285.75	46,8	V3-20-12	11R22.5
22.5x8.25	165	Ø281	10-Ø26	Ø335	47,2	V3-20-4	11R22.5
22.5x8.25	165	Ø221	8-Ø32	Ø285	46,8	V3-20-4	11R22.5
22.5x8.25	165	Ø221	10-Ø26	Ø285.75	46,8	V3-20-4	11R22.5
22.5x8.25	169	Ø281	10-Ø26	Ø335	46,1	V3-20-4	11R22.5
22.5x8.25	168	Ø220	10-Ø26	Ø285.75	47,5	V3-20-12	11R22.5
22.5x8.25	165	Ø281	10-Ø26	Ø335	48	V3-20-12	11R22.5
22.5x8.25	170	Ø221	8-Ø32	Ø285	47,5	V3-20-4	11R22.5
22.5x8.25	171	Ø281	10-Ø26	Ø335	46,2	V3-20-4	11R22.5
22.5x8.25	166	Ø281	10-Ø26	Ø335	46,2	V3-20-4	11R22.5
22.5x8.25	162	Ø221	8-Ø32	Ø285	47,5	V3-20-4	11R22.5
22.5x8.25	170	Ø221	8-Ø32	Ø285	47,5	V3-20-4	11R22.5
22.5x9.00	165	Ø281	10-Ø26	Ø335	46,5	V3-20-12	12R22.5
22.5x9.00	175	Ø281	10-Ø26	Ø335	48	V3-20-6	295R22.5
22.5x9.00	175	Ø221	8-Ø32	Ø285	48	V3-20-6	295R22.5
22.5x9.00	175	Ø222	10-Ø32	Ø285.75	48,8	V3-20-6	315/80R22.5
17.5x6.75	-12	Ø121	8-Ø17	Ø165	23	TR500	LT235/85R-16
17.5x6.75	153	Ø176	10-Ø26	Ø225	25,5	TR572C	9.5R17.5
17.5x6.75	142	Ø221	8-Ø26	Ø275	27,4	TR572	LT235/85R-16
17.5x6.00	135	164	6-Ø32.5	Ø222.25			
17.5x6.00	124	176	10-Ø26	Ø225			
17.5x6.00	134	176	10-Ø26	Ø225			
19.5x6.00	135	Ø164	6-Ø32	Ø222.25	32,1		8R19.5
19.5x6.00	135	Ø164	6-Ø32	Ø222.25	29,6	V3-20-4	8R19.5
19.5x6.75	140	Ø214	8-Ø32	Ø275	31,4	V3-20-4	8R19.5
19.5x6.75	140	Ø164	6-Ø32	Ø222.25	32,8	V3-20-4	8R19.5
22.5x11.75	0	Ø281	10-Ø26	Ø335	44	TR575	385/65R22.5
22.5x6.00	133	Ø214	8-Ø32.5	Ø275	33	V3-20-4	8R22.5
22.5x6.75	142	Ø214	8-Ø32	Ø275	32,2	V3-20-4	9R22.5
22.5x6.75	152	Ø214	8-Ø32	Ø275	40,6	V3-20-4	9R22.5
22.5x6.75	169	Ø221	10-Ø32	Ø285.75	39,6	V3-20-4	9R22.5
22.5x6.75	169	Ø281	10-Ø26	Ø335	40,7	V3-20-4	9R22.5
22.5x6.75	145	Ø214	8-Ø32	Ø275	36,5	V3-20-4	9R22.5
22.5x7.50	152	Ø214	8-Ø32	Ø275	45	V3-20-4	10R22.5
22.5x7.50	152	Ø220	10-Ø26	Ø285.75	44,5	V3-20-4	10R22.5
22.5x7.50	152	Ø221	8-Ø32	Ø285.75	44	V3-20-4	10R22.5
22.5x7.50	169	Ø221	10-Ø32	Ø285.75	44	V3-20-4	10R22.5
22.5x7.50	163	Ø221	8-Ø32	Ø285	44,3	V3-20-4	10R22.5
22.5x7.50	169	Ø281	10-Ø26	Ø335	45,6	V3-20-4	10R22.5
22.5x7.50	162	Ø221	8-Ø32	Ø285	45	V3-20-4	10R22.5
22.5x7.50	145	Ø214	8-Ø32	Ø275	45,4	V3-20-4	10R22.5
24.5x8.25	168	Ø220	10-Ø26	Ø285.75	49,6	TR574	11R24.5
24.5x8.25	168	Ø221	10-Ø32,5	Ø285.75	50,2	TR575	11R24.6